

**BAJA DESIGNS
LED LIGHT BAR
COMPARISON TABLE**

www.baja.net.au



		Dimensions & Weight				Lumens & Power			Features					Light Patterns			
		Length	Height mm	Depth mm	Weight (kg)	Lumens	Watts	Amps	Arced Option	Dimmable	Amber Backlit	Battery Management	High/Low Beam	Spot	Driving/Combo	Wide Cornering	Work/Scene
OnX6	OnX6 Plus	10"	68.3	109.0	2.0	12,460	108	8.4	No	Yes	No	Yes	Yes	Yes	Yes	Yes	No
		20"	68.3	109.0	3.6	24,920	216	16.6	No	Yes	No	Yes	Yes	Yes	Yes	Yes	No
		30"	68.3	109.0	5.2	31,910	281	21.7	Yes	Yes	No	Yes	Yes	Yes	Yes	Yes	No
		40"	68.3	109.0	6.8	38,900	346	26.8	Yes	Yes	No	Yes	Yes	Yes	Yes	Yes	No
		50"	68.3	109.0	8.5	39,430	355	28.2	Yes	Yes	No	Yes	Yes	Yes	Yes	Yes	No
	OnX6 Racer	10"	68.3	109.0	2.0	6,450	63	5.25	No	Yes	No	Yes	Yes	4 Deg	No	No	No
		20"	68.3	109.0	3.6	12,900	126	10.5	No	Yes	No	Yes	Yes	4 Deg	No	No	No
		30"	68.3	109.0	5.2	19,350	189	15.75	No	Yes	No	Yes	Yes	4 Deg	No	No	No
		40"	68.3	109.0	6.8	25,800	252	21	No	Yes	No	Yes	Yes	4 Deg	No	No	No
		50"	68.3	109.0	8.5	32,250	315	26.25	No	Yes	No	Yes	Yes	4 Deg	No	No	No
	Dual Control	30"	68.3	109.0	5.2	22,050	176	15	Yes	Dual Control	No	Yes	No	No	Yes	No	No
		40"	68.3	109.0	6.8	29,400	234	20	Yes		No	Yes	No	No	Yes	No	No
		50"	68.3	109.0	8.5	36,750	293	25	Yes		No	Yes	No	No	Yes	No	No
		60"	68.3	109.0	10.4	38,700	378	31.5	Yes		No	Yes	No	No	Yes	No	No
	Laser Hybrid	10"	68.3	109.0	2.0	7,760	95	7.6	No	No	No	Yes	Note 1	No	Yes	No	No
		20"	68.3	109.0	3.6	15,520	190	15.2	No	No	No	Yes	No	No	Yes	No	No
		30"	68.3	109.0	5.2	23,280	285	22.8	No	No	No	Yes	No	No	Yes	No	No
		40"	68.3	109.0	6.8	31,040	380	30.4	No	No	No	Yes	No	No	Yes	No	No
		50"	68.3	109.0	8.5	38,800	475	38	No	No	No	Yes	No	No	Yes	No	No
	FULL Laser	10"	68.3	109.0	1.9	3,000	90	2.69	No	No	No	Yes	No	1.5 Deg	No	No	No
		20"	68.3	109.0	3.6	6,000	180	13	No	No	No	Yes	No	1.5 Deg	No	No	No
		30"	68.3	109.0	5.2	9,000	270	19.5	No	No	No	Yes	No	1.5 Deg	No	No	No
		40"	68.3	109.0	6.8	12,000	360	26	No	No	No	Yes	No	1.5 Deg	No	No	No
		50"	68.3	109.0	8.5	15,000	450	32.5	No	No	No	Yes	No	1.5 Deg	No	No	No
	S8	S8	10"	40.6	76.2	1.1	6,350	60	4	No	No	Yes	No	No	Yes	Yes	Yes
20"			40.6	76.2	2.2	12,700	120	8	No	No	Yes	No	No	Yes	Yes	Yes	Yes
30"			40.6	76.2	3.3	19,050	180	12	No	No	Yes	No	No	Yes	Yes	Yes	Yes
40"			40.6	76.2	4.4	25,400	240	16	No	No	Yes	No	No	Yes	Yes	Yes	Yes
50"			40.6	76.2	5.4	31,750	300	20	No	No	Yes	No	No	Yes	Yes	Yes	Yes
RTL	RTL-M	6"	38.1	58.4	0.5	N/A	N/A	N/A	No	No	No	No	No	N/A	N/A	N/A	N/A
	RTL	30"	38.1	58.4	1.7	N/A	N/A	N/A	No	No	No	No	No	N/A	N/A	N/A	N/A
	RTL-S	30"	38.1	58.4	1.7	N/A	N/A	N/A	No	No	No	No	No	N/A	N/A	N/A	N/A
	RTL-B	30"	38.1	58.4	1.7	N/A	N/A	N/A	No	No	No	No	No	N/A	N/A	N/A	N/A
	RTL-G	30"	38.1	58.4	1.7	N/A	N/A	N/A	No	No	No	No	No	N/A	N/A	N/A	N/A

FIGURES FOR HI POWER.
LOW BEAM & DIMMED ARE LOWER

Note 1 * 10" OnX6 ONLY has 1 wire for LEDS, and 1 Wire for Laser



UNIT 1 - 13 ELWELL CLOSE
(Cnr Bowden Way)
BERESFIELD NSW 2322
PH 02 4966 8020
www.stottind.com.au
PO BOX 3315
THORNTON NSW 2322

Information correct at time of Printing. Subject to Change Without Notice. E&OE